





FLX S24 48 fixture lighting control console

Key Features

- Control up to 48 fixtures including LED, Moving Lights or conventionals
- 24 multi-function faders
- 49 playbacks (each with submaster & full cuestack functionality)
- 48 groups, 4 x 48 palettes (Colour, Beamshape, Position, Effect)
- 19" rackmountable (6 rack units high)
- Multi-touch interfaces for Colour & Moving LightsDedicated GO button & playback fader for
- theatrical control
- Hands-on intuitive control via 4 encoder wheels
- Free mobile apps for wireless control of your ZerOS console on iOS and Android devices
- Multi-lingual step-by-step touch screen guidance
- Art-Net 4 and sACN for network output and wireless connection to smart phone / remote monitors
- 7" multi-touch screen
- Automatic Groups, Palettes, Effects and Macros
- Colour picking, mixing & image capture
- Mood Boards by LEE Filters
- Additive, subtractive and HSV control
- Store single or multiple cues on each of the playbacks
- Built-in fixture library
- RDM compatibility
- Showfile compatibility with other ZerOS consoles
- Quiet, dust free, fanless operation
- One DMX universe, upgradable to two universes
- Two XLR Outputs (1 x 5 pin + 1 x 3 pin)
- 3 year warranty



Overview

FLX S consoles are easy to learn and simple to use - delivering all the features you need at a price you can afford. FLX S24 is flexible, offering a powerful LED and moving light controller in a small 19" unit with direct access to each of the lights in your rig.

Quickly and accurately control colour changing lights using the multi-touch colour & image picker, the encoder wheels or by selecting colours contained within a "mood" using Mood Boards by Lee Filters, and quickly record it straight onto any fader or one of the 48 instant-access colour palettes to recall later. Moving lights can be controlled using the multi-touch pan/tilt grid, the encoder wheels or with automatic effects like "Figure 8", "Rainbow" and "Fly-In".

From design to manufacture, FLX S24 and FLX S48 have been developed to work in a wide range of applications, with specific considerations for education, houses of worship, fringe theatre, community venues, corporate events, concerts, rental, fashion, festivals, holiday parks, cruise ships, TV and many more...

Built in tools such as Patch Wizard and Auto Palettes do all the prep work, getting you ready to operate quicker than ever before. Programming time is reduced with a simple three-step programming method for moving lights, colour changing and conventionals - what you want, how you want it, where you want it. And for all those really important features you need over and over again – you always have direct instant access via the dedicated Z button.



Ordering Information

0020-000022-00 0020-000026-00 0020-000030-00

2 Universe Console

0020-000023-00 0020-000027-00 0020-000031-00 FLX S24 (UK) FLX S24 (Schuko/French) FLX S24 (US)

Accessories

9805-000086-00

0021-000015-00

9802-000015-00

0020-000016-00

9805-000059-00

FLX S24 Flightcase **Replacement PSU** Wing

Supplied Accessories

External Power Supply Quick Start Guide

ZerOS software upgrade also available at: zero88.com/software/zeros/upgrade

461.00mm Dimensions 284.00mm FP-ΠÌ 00mm 00

80.00



Powering Business Worldwide

FLX S24 (US)

FLX S24 (Schuko/French)

FLX S24 (UK)

19" Rackmount ears (optional) Wing Flightcase

Software - capacity

48 Fixture Controls (using single or multiple DMX channels)

2 multipurpose USB ports (saving shows, connection of

49 Playbacks (equivalent of Cue Stacks, Submasters or Chases)

24 Multifunctional Faders (channels or playbacks, with select

Master Playback with Go Button playback and master intensity

1 Universe (upgradable to 2) over Ethernet using Art-Net 4 or sACN

4 embedded encoder wheels with select buttons

- 10,000 cues
- 4 x 48 Palettes (Colour, Beamshape, Position, Effect)
- 48 groups

Specifications

Hardware - Front Panel

or go buttons)

Hardware - Inputs/Outputs

External power supply

Internal 7" multi-touch screen

Dedicated buttons for key functions

1 5-pin XLR connector for DMX and RDM

1 3-pin XLR connector for DMX and RDM Ethernet (visualisation and Remote Apps)

accessories & Wings, software updates)

Software - features

- Integrated colour picker and "Mood Boards by LEE Filters"
- Multi touch Pan/Tilt grid
- Auto palettes, groups and fixture macros
- Gobo previews and library
- Move on Dark
- Tracking and Non-Tracking modes available
- Support for wireless remote control through handheld devices and remote monitors

Electrical

- Supply voltage range: 100 - 240V AC; MAX 2A
- Frequency: 50 60Hz
- Operating temperature: +5 to +40°C

Contact your local Eaton office

T: +44 (0)1633 838088 F: +44 (0)1633 867880 E: enquiries@zero88.com www.zero88.com

Eaton Lighting Systems

Usk House, Lakeside, Llantarnam Park. Cwmbran, Torfaen, NP44 3HD. UK eatonlightingsystems.com

© 2017 Faton All Rights Reserved

FLX_S24_Datasheet_UK_Rev1_0817

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

Eaton is a registered trademark

All other trademarks are property of their respective owners.

